


MAGIDO®

SERIES PLATINUM





In acciaio inox
En acier inoxydable
Aus edelstahl
In stainless steel
En acero inoxidable

PM400 - P600/ 2 - P1200/ 2 - P1500/ 2

- ◆ Lavapezzi a tamburo rotante pluristadio a caldo con fasi di spruzzo e immersione monovasca e plurivasca.
- ◆ Applicazioni: pulizia di fori; canali interni; e particolari con geometria complessa.
- ◆ *Rotational hot wash machine with spray and immersion cycle either single or double tank.*
- ◆ *Application: Internal channels, blind holes, and complex geometric design pieces.*
- ◆ Machine à laver avec tambour rotatif, aspersion et immersion à chaud 1 ou 2 bains.
- ◆ Application: Trous borgnes, canaux internes, pièces à géométrie complexe.
- ◆ *Maquina a tambor rotativo para el lavado en caliente con aspersion y inmersión, una o dos fases.*
- ◆ *Aplicaciones: Agujeros ciego, canales interiores y piezas complejas.*
- ◆ Reinigungsanlage mit Korbdreh- und schwenkbewegung.
- ◆ Injektionsflutwaschen und/oder Spritzwaschen in Ein- und Mehrtankausführung, beheizt.
- ◆ Anwendung: Werkstücke mit komplexer Geometrie, Sack- oder Innenbohrungen, zum Entfernen von Spänen.

MODEL	PM400	P600/ 2	P1200/ 2	P1500/ 2
Fasi di lavoro - Wash phases - Nombre de phases - Fases de lavado - Waschzonen	2	3	3	3
Dimensioni sede cesto* - Basket housing dimensions* - Dimensions siege panier* - Dimensiones sede cestas* Nutzbare Arbeitsabmessungen*	mm 450x350x200	mm 650x300x200	mm 1200x500x500	mm 1500x800x860
N° cesti - N° Basket - Qtè panier par cycle - Cantidad cestas por ciclo - Korbanzahl pro Waschgang	2*	1*	1*	1*
Carico ammissibile - Load Weight - Charge utile- Carga maxima - Beladegewicht	Kg 50	Kg 200	Kg 500	Kg 700
Altezza carico - Load edge - Hauteur de chargement - Altura de carga - Beladehöhe	mm 1200	mm 920	mm 1000	mm 1120
Vasca Lavaggio - Tank wash - Bain de lavage- Tanque lavado - Inhalt Waschtank	Lt 600	Lt 500	Lt 1200	Lt 2500
Vasca risciacquo - Tank Rinse - Bain de rinçage -Tanque aclarado - Inhalt Spültank	-	Lt 250	Lt 500	Lt 800
Temperatura - Temperature - Temperatur	°C 20-70	°C 20-70	°C 20-70	°C 20-70
Riscaldamento lavaggio - Wash heat - Chauffage lavage - Calefacción lavado - Heizung Waschtank	Kw 24	Kw 18	Kw 30	Kw 60
Riscaldamento risciacquo - Rinse heat - Chauffage de rinçage - Calefacción aclarado - Heizung Spültank	-	Kw 12	Kw 18	Kw 30
Pompa lavaggio - Wash pump - Pompe lavage - Bomba lavado - Waschpumpe	Kw 7,5	Kw 3	Kw 4	Kw 5,5
• Portata /pressione - Flow rate / Pressure- Debit/ Pression- Caudal/pression - Durchflussmenge / Druck	lt/min Bar 300/6	lt/min Bar 250/4	lt/min Bar 350/4	lt/min Bar 500/4
Pompa risciacquo - Rinse pump - Pompe rinçage - Bomba aclarado - Spülpumpe	Kw 4	Kw 3	Kw 4	Kw 5,5
• Portata/ Prevalenza - Flow rate/ Pressure - Debit/ Pression - Caudal/Pression Durchflussmenge / Druck	-	lt/min Bar 120/4	lt/min Bar 300/4	lt/min Bar 500/4
Aspiratore vapori - Exhaust fan - Extracteur vapeurs - Aspirador de vapores - Abzugsventilator	Kw 0,18	Kw 0,09	Kw 0,18	Kw 0,37
• Portata - Outlet- Debit - Caudal • Durchsatzmenge	m³/h 300	m³/h 100	m³/h 300	m³/h 600
Rotazione cesta - Basket rotation - Rotation Panier - Rotacion cesta Korbantrieb - Umdrehungen pro Minute	Kw 0.18 rpm 1-3	Kw 0.18 rpm 1-3	Kw 0.75 rpm 0,5 ÷ 2,5	Kw 0.75 rpm 0,5 ÷ 1,5
Alimentazione- Voltage - Alimentation électrique - Alimentación eléctrica - Elektr. Anschluss	400V 3ph + N	400V 3ph + N	400V 3ph + N	400V 3ph + N
Potenza Max Assorbita - Power requirement - Puissance installé - Potencia maxima - Stromaufnahme	Kw 32	Kw 34	Kw 53	Kw 90
Dimensioni d'ingombro max - Machine dimensions - Encombrement machine - Dimensiones maxima -Gesamtabmessungen	mm 2500x2000x2700	mm 1350x2300x2200	mm 1600x3400x2500	mm 2500x6000x4200
Dimensioni trasporto -Shipping dimensions - Dimension pour transport - Dimensiones para transporte - Transportabmessungen	mm 2500x2000x2600	mm 1350x1700x2200	mm 1600x2200x2300	mm 2500x4000x2800
Peso - Dry weight - Poids - Peso - Leergewicht	Kg 1200	Kg 1000	Kg 1500	Kg 2500

* Cesto escluso / Basket not included / Panier pas compris / Cesta no incluyda / Korb nicht eingeschlossen

OPTIONAL				
Coibentazione	Insulation	Calorifugeage	Calorifugado	Isolierung
Asciugatura	Dry	Séchage	Secado	Trocknen
Soffiaggio	Blow off	Soufflage	Soplado	Abblasen
Disoleatore	Oil skimmer	Déshuileur	Separador de aceite	Ölskimmer
Filtro(50-300)µm	Filter (from 50-300) µm	Filtre de (50 - 300) µm	Filtros (desde 50 hasta 300) µm	Filter (Feinheit 50 bis 300) µm
Cesto*	Basket*	Panier*	Cesta*	Korb*

La società si riserva di apportare modifiche in qualsiasi momento - Nous reservons les droits de modifications - Technische Änderungen vorbehalten - We reserve the right to modify without notice - Nuestra empresa se reserva el derecho de realizar modificaciones en cualquier momento.